

Florida Short Term Radon Test Project Data Sheet

*Indicates the information which must be provided to comply with FL DOH regulations. Failure to complete will delay reporting!

*Tester Name Placing Devices: _____ *Certified Tester # _____ *Signature: _____

*Tester Name Retrieving Devices: _____ *Certified Tester # _____ *Signature: _____

*(circle one) Owner or Certified Tester *Both Placed and Retrieved Signatures are required to receive results

Send Written Report To:

Property Tested:

Company Name _____

*Site Name or Owner: _____

Address _____

*Test Address: _____

City _____ State _____ ZIP _____

*City: _____ *County: _____ *State: _____ *ZIP: _____

Telephone # _____ Email _____

*Age of Building: _____ *Year Built: _____

Additional Emails: _____

*# of Stories of Building: _____ *# of Stories Occupied: _____

*# of Buildings on Property: _____ *# of Buildings Tested: _____

Lab Use Only	Serial/Sample #	*Start Date	*Stop Date	*Start Time AM/PM	*Stop Time AM/PM	*Building	*Unit	*Floor Tested	*Name of Room	*Duplicate Blank or Standard	Lab Use Only

Additional Building & Test Information

*Building Type #1 (circle one) Residential Non-Residential Day Care Home Day Care Center Foster Care Home Public School Private School Other _____
 *Building Type #2 (circle one) Unattached Attached Residential *Building Type #3 (circle one) Multi Level Single Level *Structure Type (circle one) Basement Crawlspace Slab on Grade Pier Other
 *Test Purpose (circle one) Initial Screening Pre Mitigation Post Mitigation Real Estate Transaction Follow Up
 *Closed House Conditions Present at Start of Test? YES or NO *Present at End of Test? YES or NO
 *Indoor Temperature Cold (<65°F) Normal Hot (>75°F) Actual _____ F Indoor Humidity Dry (<25 % rH) Normal Humid (>60 % rH) Actual _____ rh
 *Cooling System: (circle one) Central AC Room AC Window Fan Attic Fan Other *In Use: YES or NO *Heating System (circle one) Gas Electric Wood Space Heat *In Use YES or NO

Send Test Devices To: AccuStar Labs | 6951 Allentown Blvd, Suite N, Harrisburg PA 17112 | Tel: (800) 523-4964 Fax: (717) 274-5662

FL RB2125, RB2032

Doc Rev #3 -11/3/2022

ACCUSTAR LABS – HARRISBURG PA
FLORIDA SHORT TERM TESTING INSTRUCTIONS FOR RADON MEASUREMENT
LARGE BUILDINGS/AREAS – COMPLEX, ETC

IMPORTANT NOTICE CERTIFIED FLORIDA RADON TESTERS: FLORIDA DOH REQUIRES THAT CERTIFIED TESTERS BE AFFILIATED WITH ACCUSTAR LABS PRIOR TO USING THEIR PRODUCTS. WE CAN NOT REPORT RESULTS IF YOU ARE NOT AFFILIATED WITH MEB# 2125

Read all instructions completely before starting tests.

Failure to follow instructions and completely fill out all information on data sheets will prohibit analysis. If you have any questions call AccuStar Labs before you begin measurement. (800) 523-4964.

Scheduling: Prepare for Testing

1. INCLUDE 10% DUPLICATES AND 5% FIELD BLANKS.
2. Tests should not be conducted during severe weather conditions, such as storms with high winds or barometric changes. Check your local weather forecast to ensure measurement is scheduled during satisfactory weather conditions.
3. Tests should not be conducted while building is undergoing remodeling or other modifications, including HVAC system modifications.
4. Closed house/building conditions must be maintained. All windows and external doors should remain closed (except for brief opening of doors necessary for normal entry and exit) FOR 12 HOURS PRIOR TO AND DURING MEASUREMENT PERIOD.

RESULTS WILL BE INVALID IF CLOSED HOUSE CONDITIONS ARE NOT MAINTAINED.

5. Air exchange systems (other than furnaces) should not be operation for 12 hours prior to and during testing.
6. **ACCUSTAR LABS RECOMMENDS 48 HOURS EXPOSURE.**
Exposure of less than 48 hours or more than 96 hours will invalidate results.

Placement

1. As a guideline, the canisters should be placed at a minimum of one can every 2000 square feet of open space.
2. Do NOT place canisters in bathrooms, kitchens, boiler rooms, closets or storage areas. Place in the lowest regularly used areas of the structure, exposed to the air people breathe.
3. Keep canisters away from excessive heat, outside walls, and/or drafts caused by HVAC vents, windows, doors, direct sunlight and high humidity.

Starting the Test

1. Remove the vinyl tape and lid from canister, place lid on the bottom of the canister and using the tape attach lid to the bottom, this way the can and lid will always correspond, and tape will not be misplaced. Do not let the tape pick up any debris; tape must be used to reseal the canister.
2. Record the serial number and the test site information on the information forms provided. (Missing information will prohibit analysis). *Information forms other than the ones provided must be pre-approved to receive priority status and timely results.*
3. Record the start date and complete start time (including AM or PM). **Sign Data Sheet.**
4. Florida testers must provide a Florida-DOH Certification Number. Certified testers must completely perform all testing procedures (place/retrieve and ship canisters).
5. Place the canisters open side up, exposing it to the air. Do not cover or block canisters. Keep at least 4 inches from other objects. At least 2 feet off the floor and 1 foot from the ceiling.
6. **Inform clients of testing conditions and protocols.** Discrepancies should be documented.

Important Note! Missing or incorrect exposure information (dates and times) may be recalculated if information is provided in a timely manner. If a recalculation is requested, there will be a \$10.00 fee per canister. Payment - Pre Paid - MC/VISA/AMEREXP – Results may still be non-certified due to other discrepancies. Please check in advance before requesting a recalculation.

Ending the Test

1. After exposing the canisters 48 hours (exposure limit is 96 hours), replace the lid and completely reseal the canister with the vinyl tape (use electrical tape if vinyl tape is misplaced.) **The canister must be re-taped around the seam the same way as when it was opened.**
2. Record the stop date and complete time (including AM or PM). **Sign Data Sheet.**
3. **Make sure ALL information is completely filled out. Missing information will prohibit analysis. Make sure both signatures are provided.**

Returning the canisters for Analysis (we recommend you make copies of information forms for your records)

1. Place 1 to 10 canisters in plastic sleeve provided or other plastic bags. Include the corresponding information form.
2. *Please do not just throw large amounts of canisters in a box, keep them separated with info sheets. Loose canisters will cause a delay with your results.*
3. Make sure completed corresponding paperwork accompany canisters.
 - We will not call for missing information. (If a recalculation is requested due to missing or incorrect exposure dates or times there is a \$10.00 recalculation fee per canister.)
 - **CHECK THAT ALL INFORMATION IS COMPLETED-CIRCLED-ETC. WE WILL NOT REPORT RESULTS IF ANY INFORMATION IS MISSING.**
4. **MAIL CANISTERS IMMEDIATELY- LABORATORY MUST RECEIVE CANISTERS WITH IN 8 DAYS AFTER SEALING. A DELAY WILL PROHIBIT ANALYSIS!**

CHECKLIST

- Satisfy measurement conditions – follow placement instructions.
- MAKE SURE REQUIRED AMOUNT OF DUPLICATES AND BLANKS ARE INDICATED.
- Remind client to maintain proper testing conditions.
- Expose canisters the recommended 48 hours. NO less than 48. NO more than 96 Hours.
- Seal detectors completely around canisters seam with vinyl tape.
- MAKE SURE ALL INFORMATION IS PROVIDED.
- Make sure canisters are separated and information forms accompany corresponding canisters.
- Ship IMMEDIATELY to AccuStar Labs. Canisters must be received within 8 days for analysis

Shipping Address:
(UPS – FedEx – Etc.)
6951 Allentown Blvd, Suite N
Harrisburg, PA 17112

Mailing Address:
(Post Office Delivery)
PO Box 6994
Harrisburg, PA 17112

AccuStar Labs
(800) 523-4964 | Tel: (717) 274-8310 | Fax: (717) 274-5662
Email: radonlabpa@accustarlabs.com

Questions or comments concerning the information required should be directed to Florida-DOH (800) 543-8279
Limitation of Data and Liability - We maintain all data and other information strictly confidential and will not release it to other than Authorized Representatives of AccuStar Labs, without specific permission from the customer except where required by law. Information may be included in reports to the public but without reference to specific names/addresses. We do not accept responsibility for financial or health consequences of subsequent action taken by our customer or his consultants as a result of this analysis and sampling. We make NO warranty of any kind, express or implied for the consequences of erroneous test results. Neither AccuStar Labs, nor any of its employees or agents shall be liable under any claim, charge or demand whether in contract, tort or otherwise, for any and all loss, cost, charge, claim demand, fee, expense or damage of any nature or kind arising out of, connected with, resulting from or sustained as a result of any radon testing requests. Test kits are analyzed by AccuStar Labs using the information provided by the customer/tester. AccuStar Labs is not responsible if correct information is not provided or if test instructions were not followed.